



Overview

- EM-Marin Card format /125KHz.
- Support 2000 users and management card , Easy management.
- Operating Voltage: 12VDC.
- Current Drain: <90mA.
- Opening Mode: Card.
- With Lock relay output, NO/NC output.
- Support management card easy to add user card and delete user card.
- Wiegand input, Multi-function device, Support external WG26 card reader.
- Programming through keypad.

Features

- 1.Metal case anti-smash and anti-explosion it can be installed outdoor.
- 2. Management card can add or delete user cards easily, convenient operation.
- 3. Wiegand input multi-function device, support external WG26 card reader.
- 4. Multiple function, NO/NC reed from alternative, light flickers when read cards.
- 5.Remote control can drive lock, use keypad to program function.







AX-108M

Metal Card Access Controller With Keypad

Specification

Model	AX-108M
card type	EM (ID) card (IC card for options)
Operating Voltage	DC 12V±10%
Opening Mode	Card, remote control
Wiegand Signal	Wiegand Input, Support External WG26 Card Reader
Storage	2000 User Card
Ambient Temperature	0°C~60°C
Ambient Humidity	20%~80%
Access Control Interface For	3rd Party Electric Lock, Exit Button, Door Sensor
Card Reading Distance	1-15cm
Waterproof	Confirms to IP65
Management	With Remote Control Management Card to Add / Delete Card
Dimension	135*58*22mm
Gross Weight	0.58kg



