

# AX-1200MW

## Outdoor Gate Lock

- Voltage:DC12V or DC24V.
- Waterproof IP65.
- Holding Force: 600kg (1200Lbs).
- Lock Size: 266L\*67W\*39H (mm).
- Armature Plate:185L\*57W\*13H (mm).
- Current Draw: 12V/500mA 24V/250mA.
- With Buzzer Customization Available.



### Overview

AX-1200MW single door waterproof outdoor gate lock, specially used to out glass door, wodden door, metal door, fire doors, and all kinds of door. Hoisting design, saves time and power when installation. Inward door, frameless glass door, narrow door all have a complete set of accessories. Special Anti-residual magnetic design makes automatic access control safer.

### Features

- 1.Wear materials, durable.
- 2.waterproof, whole sealing treatment.
- 3.Suitable for Indoor and outdoor.
- 4.lock body with double insulation treatment.
- 5.Waterproof, outdoor gate lock, passed 1200lbs super static linear tension tests.
- 6.Anti-residual magnetic design, keep constant tension.
- 7.Electromagnetic suction work completely, there is no mechanical failure.
- 8.Shell with high strength alloy material, anode hardening treatment.
- 9.Through the European CE and ROHS, MA certification in China.
- 10.Built-in reverse current protection device (MOV), performance stability, safety coefficient is higher.



**AX-1200MW**

Specification

Model	AX-1200MW
Holding Force	600kg (1200lbs)
Waterproof grade	IP65
Lock Status Sensors	Dry contact NO,NC,COM
Rated Operating Voltage	12/24VDC
Current consumption	12V/600mA 24V/300mA
Optional Functions	Relock Delay Timer,Buzzer
Surface finish for magnet	Zinc plated
Surface finish for armature plate	Zinc plated
Ambient temperature in °C	-10~+55°C (14-131F)
Suitable for	Wooden , Aluminum , Glass , Fireproof & Metal
Magnets Dimensions (L x W x D)	265L*71W*40H (mm)
Armature Plate Dimensions (L x W x D)	185L*5760W*13H (mm)
Weight in kg	4.5kg
CE-mark for building	Yes
Rohs-mark for building	Yes

