

AX-350LSW

Small Magnetic Lock

- With signal output.
- Voltage: DC12V or DC24V.
- LED & Waterproof IP65 Customization Available.
- Holding Force: 180kg (350Lbs).
- Lock Size: 170L*35W*21H (mm).
- Armature Plate: 130L*33W*9.3H (mm).
- Current Draw: 12V/500mA 24V/250mA.
- No residual magnetism, no mechanical damage 90 degrees open for all kinds of doors with frame.



Overview

AX-350LSW, single door small magnetic lock, with the door state signal feedback, specially used to normal glass door, wooden door, metal door, fire doors, small doors. Hoisting design, saves time and power when installation. Inward door, frameless glass door, narrow door all have a complete set of accessories. Special Anti-residual magnetic design makes automatic access control safer and more convenient.

Features

1. With the door state signal feedback, passed 350lbs super static linear tension tests.
2. Anti-residual magnetic design, keep constant tension.
3. Built-in reverse current protection device (MOV), performance stability, safety coefficient is higher.
4. Wear materials, durable.
5. Electromagnetic suction work completely, there is no mechanical failure.
6. Shell with high strength alloy material, anode hardening treatment.
7. Lock body with double insulation treatment.
8. Through the European CE and ROHS, MA certification in China.



AX-350LSW

Small Magnetic Lock

Specification

Model	AX-350LSW
Holding Force	180kg (350lbs)
Lock Status Sensors	NO,NC,COM
Optional Functions	LED, Relock Delay Timer, Buzzer
Rated Operating Voltage	12/24VDC
Surface finish for magnet	Zinc plated
Surface finish for armature plate	Zinc plated
Ambient temperature in °C	-10~+55°C (14-131F)
Suitable for	Wooden , Aluminum , Glass , Fireproof & Metal
Magnets Dimensions (L x W x D)	170L*35W*21H (mm)
Armature Plate Dimensions (L x W x D)	130L*33W*9.3H (mm)
Weight in kg	1.1kg
CE-mark for building	Yes
Rohs-mark for building	Yes
Current consumption	500mA / 12V or 250mA / 24V

Related Images

