

AX-600LSWB

600Lbs Magnetic Door Lock

- Holding Force: 280kg (600Lbs).
- Lock Size: 250L*48W*25H (mm).
- Armature Plate:180L*38W*11H mm).
- Current Draw: 12V/500mA 24V/250m.
- LED indicates the door is unlock,Green indicates the door is lock.
- No residual magnetism, no mechanical damage 90 degrees open for all kinds of doors with frame With Buzzer Customization Available.



Overview

AX-600LSWB wooden door, metal door, fire doors, small doors, the most widely used. Hoisting design, saves time and power when installation. Inward door, frameless glass door, narrow door all have a complete set of accessories. Special Anti-residual magnetic design makes automatic access control safer and more convenient.

Features

- 1.Wear materials, durable.
- 2.Lock body with double insulation treatment.
- 3.Anti-residual magnetic design, keep constant tension.
- 4.Built-in reverse current protection device (MOV), performance stability, safety coefficient is higher.
- 5.Electromagnetic suction work completely, there is no mechanical failure.
- 6.Shell with high strength alloy material, anode hardening treatment.
- 7.Through the European CE and ROHS, MA certification in China.
- 8.With LED (double color indicate), has door status signal output, passed 600lbs super static linear tension tests.



AX-600LSWB

600Lbs Magnetic Door Lock

Specification

Model	AX-600LSWB
Holding Force	280kg (600Lbs)
Lock Status Sensors	NO, NC, COM
Optional Functions	Relock Delay Timer, Buzzer
Rated Operating Voltage	12/24VDC
Surface finish for magnet	Zinc plated
Surface finish for armature plate	Zinc plated
Ambient temperature in °C	-10~+55°C (14-131F)
Suitable for	Wooden , Aluminum , Glass , Fireproof & Metal
Magnets Dimensions (L x W x D)	250Lx48Wx25H(mm)
Armature Plate Dimensions (L x W x D)	180L*38W*11H(mm)
Weight in kg	2.0kg
CE-mark for building	Yes
Rohs-mark for building	Yes
Current consumption	12V/500mA 24V/250mA

Related Images

