

AX-600SW

Waterproof Magnetic Lock

- Fail-safe: Power to lock.
- Lock Size: 222L*47.2W*26H (mm).
- Armature Plate: 180L*38W*11H (mm).
- Holding Force: 280kg (600Lbs).
- Voltage: 12 or 24VDC.
- Current Draw: 12V/480mA.
- Suitable for: Wooden door , Glass door ,Metal door, Fireproof door.



Overview

AX-600SW single door embedded magnetic lock, Stainless steel, Waterproof, specially used to out glass door, wodden door, metal door, fire doors, sliding door. Hoisting design, saves time and power when installation , use magnetic force to catch up door leaf, safe and reliable. Inward door, frameless glass door, narrow door all have a complete set of accessories. Special Anti-residual magnetic design makes automatic access control safer and more convenient.

Features

1. Waterproof, outdoor magnetic lock, passed 600lbs super static linear tension tests.
2. Anti-residual magnetic design, keep constant tension.
3. Built-in reverse current protection device (MOV), performance stability ,safety coefficient higher.
4. Wear materials, durable.
5. Electromagnetic suction work completely, there is no mechanical failure.
6. Shell with high strength alloy material, anode hardening treatment.
7. lock body with double insulation treatment.
8. Through the European CE and ROHS, MA certification in China.



AX-600SW

Waterproof Magnetic Lock

Specification

Model	AX-600SW
Holding Force	280kg (600Lbs)
Waterproof grade	IP65
Lock Status Sensors	NO
Rated Operating Voltage	12/24VDC
Current consumption	12V/480mA
Optional Functions	Relock Delay Timer,Buzzer
Surface finish for magnet	Stainless steel
Surface finish for armature plate	Stainless steel
Ambient temperature in °C	-10 ~ +55°C (14-131F)
Suitable for	Wooden & Aluminum & Glass & Fireproof & Metal
Magnets Dimensions(L x W x D)	222L*47.2W*26H(mm)
Armature Plate Dimensions(L x W x D)	180L*38W*13H(mm)
Weight in kg	1.95kg
CE-mark for building	Yes
Rohs-mark for building	Yes

