

# AX-800LSWB

## Electromagnetic Gate Lock

- With LED and signal output.
- Voltage:DC12V or DC24V.
- Waterproof IP65 Customization Available.
- Lock Size: 280L\*49W\*29H(mm).
- Current Draw: 12V/500mA 24V/250mA.
- LED indicates the door is unlock,Green indicates the door is lock.
- No residual magnetism, no mechanical damage 90 degrees open for all kinds of doors with frame With Buzzer Customization Available.



### Overview

AX-800LSWB, single door magnetic lock, with door status signal output and led indicate, specially used to normal glass door, wodden door, metal door, fire doors, and all kinds of door. Hoisting design, saves time and power when installation. Inward door, frameless glass door, narrow door all have a complete set of accessories. Special Anti-residual magnetic design makes automatic access control safer and more convenient.

### Features

- 1.With the door status signal output, passed 800lbs super static linear tension tests.
- 2.Anti-residual magnetic design, keep constant tension.
- 3.Built-in reverse current protectiondevice (MOV), performance stability, safety coefficient is higher.
- 4.Wear materials, durable.
- 5.Electromagnetic suction work completely, there is no mechanical failure.
- 6.Shell with high strength alloy material, anode hardening treatment.
- 7.Lock body with double insulation treatment.
- 8.Throughthe European CE and ROHS, MA certification in China.



## AX-800LSWB

## Electromagnetic Gate Lock

### Specification

Model	AX-800LSWB
Holding Force	380kg (800Lbs)
Lock Status Sensors	NO,NC,COM
Optional Functions	LED, Relock Delay Timer,Buzzer
Rated Operating Voltage	12/24VDC
Surface finish for magnet	Zinc plated
Surface finish for armature plate	Zinc plated
Ambient temperature in °C	-10~+55°C (14-131F)
Suitable for	Wooden, Aluminum, Glass, Fireproof & Metal
Magnets Dimensions (L x W x D)	285Lx55Wx29H (mm)
Armature Plate Dimensions (L x W x D)	190Lx45Wx11H (mm)
Weight in kg	2.6kg
CE-mark for building	Yes
Rohs-mark for building	Yes
Current consumption	12V/500mA 24V/250mA
Lock Status Indicator	Red and Green, double color LED

### Related Images

