

AX-800TDSB EM lock with Timer Dealy

- With delay and signal output.
- Voltage:DC12V or DC24V.
- Armature Plate:190L*45W*11H(mm).
- Current Draw: 12V/500mA 24V/250mA.
- LED indicates the door is unlock, Green indicates the door is lock.
- With Buzzer
- No residual magnetism, no mechanical damage 90 degrees open for all kinds of doors with frame.

Overview

AX-800TDSB, single door waterproof magnetic lock, with the door status signal output, led indicates time delay and buzzer, specially used to normal glass door, wodden door, metal door, fire doors, and all kinds of door. Hoisting design, saves time and power when installation. Inward door, frameless glass door, narrow door all have a complete set of accessories. Special Anti-residual magnetic design makes automatic access control safer.

Features

1. With door status signal feedback and time delay and buzzer, passed 800lbs super static linear tension tests.

2.Anti-residual magnetic design, keep constant tension.

3.Built-inreverse current protection device (MOV), performance stability ,safety coefficient is higher.

4.Wearmaterials, durable.

5. Electromagnetic suction work completely, there is no mechanical failure.

6.Shell with high strength alloy material, anode hardening treatment.

7.Lock body with double insulation treatment.

8. Through the European CE and ROHS, MA certification in China.





AX-800TDSB

EM lock with Timer Dealy

Specification

| Model | AX-800TDSB |
|---------------------------------------|---|
| Holding Force | 380kg (800Lbs) |
| Lock Status Sensors | NO,NC,COM |
| Optional Functions | Relock Delay Timer |
| Rated Operating Voltage | 12/24VDC |
| Surface finish for magnet | Zinc plated |
| Surface finish for armature plate | Zinc plated |
| Ambient temperature in °C | -10∼+55°C (14-131F) |
| Suitable for | Wooden , Aluminum , Glass , Fireproof & Metal |
| Magnets Dimensions (L x W x D) | 285Lx55Wx29H (mm) |
| Armature Plate Dimensions (L x W x D) | 190Lx45Wx11H (mm) |
| Weight in kg | 2.6kg |
| CE-mark for building | Yes |
| Rohs-mark for building | Yes |
| Current consumption | 12V/500mA 24V/250mA |
| Lock Status Indicator | Red and Green, double color LED |
| Buzzer | When lock abnormal,provide buzzer alarm |

Related Images







